

Inspecta Latvia (notified body No.1325) confirms that in compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product:

Precast concrete products:

**precast concrete monolithic stairs for use in loadbearing
external and internal stairs, series „K”,
according to Annex**

PRODUCED BY THE MANUFACTURER:

SIA „SKONTO PREFAB”

ADDRESS:

Granīta iela 33 k-4, Acone, Salaspils l.t., Salaspils nov., LV-2119, Latvia; Reg. No. 40003610650

ADDRESS OF MANUFACTURER:

SIA „SKONTO PREFAB”, Granīta iela 33 k-4, Acone, Salaspils l.t., Salaspils nov., LV-2119, Latvia

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard


EN 14843:2007

Under system 2+ are applied and that
the factory production control fulfils all the prescribed requirements set out above.

CERTIFICATE ISSUED ON: 29.07.2015.


Mārtiņš Maskavs

Certification Manager



Certificate first was issued on the 29th July 2015 (supersedes certificate No.1325-CPD-1719) and will remain valid as long as the test methods and/or factory production control requirements included in the harmonised standard, used to assess the performance of the declared characteristics, do not change, and the product, and manufacturing conditions in the plant are not modified significantly.

Certificate is issued on 1 (one) page
and it encloses Annex on 1 (one) pages

AS "Inspecta Latvia"
Skanstes iela 54A, Rīga
LV-1013, Latvija
Tālr. +371 67 607 900




CEOC
INTERNATIONAL

Precast concrete monolithic stairs for use in loadbearing external and internal stairs according to EN 14843:2007

Characteristics	Declared properties of product	
	min.	max.
Declaration method	method 3	
Name of type (code)	K	
Name of element according to EN 14843 Annex A	Stairs flight	
Concrete		
compressive strength ($f_{ck, cyl}/f_{ck, cube}$), N/mm ²	C25/30	C30/37
Reinforcing steel:		
ultimate tensile strength (f_{tk}), N/mm ²	648	659
tensile yield strength (f_{yk}), N/mm ²	581	591
Durability of product		
freeze resistance (F), cycles	-	50
Detailing of product		
length, mm	2000	3080
weight, mm	600	1500
heights, mm	1200	1950
corbel or lap joint length, mm	100	120
corbel or lap joint heights, mm	100	150
technical draft No	According to design specification	

Mārtiņš Maskavs
Certification Manager



Annex issued on 1 (one) page

